



ISO 9001:2000 CERTIFIED

BAR'S LEAKS TECHNICAL BULLETIN

Tech Bulletin #: TB-1201-1

Page 1 of 1

Date 1st Issued: June 6, 2006

Date Revised: April 14, 2008

Bar's Leaks Super Radiator Flush

Part #: 1201

SUPER RADIATOR FLUSH

Bar's Leaks Radiator Flush will help your cooling system by removing deposits that build up over time causing overheating. Cleans dirty systems factory clean. Fast, easy and safe to use. Non-acid formula is safe to use on all cooling system materials. Harmless to all parts of the cooling system, including copper and aluminum. Use every time changing antifreeze



MOST COMMON DIRTY COOLING SYSTEM PROBLEMS

- Overheating
- Deposits & Build Ups

THE SOLUTION, BAR'S LEAKS SUPER FLUSH

- Cleans System
- Removes Build Up

DIRECTIONS

1. Allow engine to cool. Drain system. Close drain.
2. Add entire contents of bottle and refill system with water. For larger cooling systems, use one bottle of Super Radiator Flush for every 4-gallons. Reinstall cap.
3. Drive for 3 to 6 hours (normal driving) for best results. NOTE: This may be done over several days. If outside temperature is below freezing, this needs to be done in one day to prevent cooling system damage.
4. Allow engine to cool. Flush cooling system and reservoir until water runs clear.
5. Close drain. Refill cooling system and reservoir with manufacturer's recommended antifreeze/water mixture.

Part Number: 1201
 UPC Item: 0 46087 01201 7
 UPC Case: 1 00 46087 01201 4
 Bottle Size: 22 fl. oz. (651 ml)
 Bottle Dimensions: 4.5 x 2.0 x 7.4
 Bottle Cube: 67
 Case Pack: 6 bottles per case
 Case Size: 9.4 x 6.4 x 7.9
 Case Cube: 475
 Case Weight: 11.5 pounds
 Pallet: TI 30 HI 6 Total 180
 Pallet Height: 52 inches
 Tariff Code: 3405.90.0000

Dosage

Use one bottle of Super Radiator Flush for every 4-gallons.