



ISO 9001:2000 CERTIFIED

BAR'S LEAKS TECHNICAL BULLETIN

Tech Bulletin #: TB-1211-1

Page 1 of 1

Date 1st Issued: June 6, 2006

Date Revised: April 14, 2008

Bar's Leaks 10 Minute Flush

Part #: 1211

10 MINUTE FLUSH

Bar's Leaks Radiator Flush will help your cooling system by removing deposits that build up over time causing overheating. Cleans dirty systems factory clean. Fast, easy and safe to use. Non-acid formula is safe to use on all cooling system materials. Harmless to all parts of the cooling system, including copper and aluminum. Use every time changing antifreeze



MOST COMMON DIRTY COOLING SYSTEM PROBLEMS	THE SOLUTION, BAR'S LEAKS SUPER FLUSH
<ul style="list-style-type: none"> • Overheating • Deposits & Build Ups 	<ul style="list-style-type: none"> • Cleans System • Removes Build Up

DIRECTIONS

1. Allow engine to cool. Drain system. Close drain.
2. Add entire contents of bottle and refill system with water. Reinstall cap.
3. After engine reaches normal operating temperature, run engine for 10 minutes with heater on and air conditioner off.
4. Allow engine to cool. Flush cooling system and reservoir until water runs clear.
5. Close drain. Refill cooling system and reservoir with manufacturer's recommended antifreeze/water mixture.

Part Number: 1211
 UPC Item: 0 46087 01211 6
 UPC Case: 1 00 46087 01211 3
 Bottle Size: 12 fl. oz. (355 ml)
 Bottle Dimensions: 2.8 x 2.8 x 5.8
 Bottle Cube: 45
 Case Pack: 6 bottles per case
 Case Size: 8.5 x 5.9 x 6.3
 Case Cube: 316
 Case Weight: 5.6 pounds
 Pallet: TI 37 HI 6 Total 222
 Pallet Height: 42 inches
 Tariff Code: 3402.11.0000

Dosage

1 bottle treats a standard passenger vehicle/ light truck. Use every time you change your antifreeze.