



ISO 9001:2000 CERTIFIED

RISLONE TECHNICAL BULLETIN

Tech Bulletin #: TB-4416-1

Page 1 of 1

Date 1st Issued: March 22, 2007

Date Revised: November 19, 2009

Rislone Ring Seal

Part #: 4416

RING SEAL

Rislone Ring Seal is formulated to help stop exhaust smoke, reduce oil burning and prevent plug fouling caused by “blow-by”. Blow-by is usually caused by gaps in internal engine parts resulting from excess wear. Ring Seal contains viscosity improvers that thicken the oil film filling these gaps.

- Contains high-shear polymers which provide a seal for worn pistons & rings to stop blow-by.
- Cushions and coats engine parts helping to reduce wear and quiet noisy lifters.
- Retains oil flow characteristics in hot and cold weather.
- Works with all gasoline and diesel engines using conventional, high mileage and synthetic oil.



TEST	ASTM	TYPICAL PROPERTIES
Specific Gravity @ 15.6°C	D-1298	0.8581
API Gravity	D-1298	33.4
Flash Point PMCC	D-93	208°C / 406°F
Viscosity, cSt. @ 100°C	D-445	353
Viscosity, cSt. @ 150°C	D-445	n/a
Pour Point °C	D-97	-25

DIRECTIONS:

Bring engine up to normal operating temperature. Add entire bottle of Ring Seal to engine crankcase at or between oil changes. Idle or drive engine for 5 minutes after installation.

One bottle treats 4 to 6 quarts of engine oil. Add Ring Seal every 2,000 miles or with every oil change.

Part Number:	4416
UPC Item:	0 78615 04416 0
UPC Case:	1 00 78615 04416 7
Bottle Size:	16 fl. oz. (472mL)
Bottle Dimensions:	3.5 x 1.8 x 7.6
Bottle Cube:	48
Case Pack:	6 bottles per case
Case Size:	7.4 x 5.7 x 8.0
Case Cube:	337
Case Weight:	6.5 pounds
Pallet:	TI 40 HI 5 Total 200
Pallet Height:	45 inches
Tariff Code:	3811.21.0000

Dosage

1 bottle treats 4 to 6 quarts of oil