

## FREQUENTLY ASKED QUESTIONS

### TRANSMISSION STOP SLIP WITH LEAK REPAIR

#### P/N 4502, 4502-5, 4502-55

*How does Rislone Transmission Stop Slip with Leak Repair Work?*

Rislone Transmission Stop Slip with Leak Repair contains a special blend of viscosity improvers, anti-wear friction modifiers and extreme pressure performance additives to solve most transmission problems. These additives reduce rough shifting and friction, while eliminating slip, controlling temperature, and repairing shudder, chatter and whining.

*How long does it take to start working?*

Depending on the transmission problem, results will either be immediate or noticeable within a few days of driving.

*If first application does not completely solve my problem, may I add another bottle?*

Yes, for severe problems or badly worn transmissions, use double the dosage or a second bottle.

*Will Rislone Transmission Stop Slip with Leak Repair work in my vehicle?*

Yes, it works with any front wheel drive, rear wheel drive, all-wheel drive and four wheel drive transmissions. Use in ALL light duty and heavy duty vehicles including; car, truck, van, SUV, and RV's with any 3 speed, 4 speed, 5 speed, 6 speed, electronic, overdrive, automatic or manual transmission.

*Is it compatible with synthetic formulas?*

Yes, it is compatible with ALL types of domestic and import transmission fluid; including petroleum and synthetic formulas.

*Can I add to my existing transmission fluid?*

Yes, remove transmission dipstick and check fluid level. For most vehicles this is usually done while the engine is running and the transmission is in park. Tip: The transmission dipstick is usually located near the engine oil dipstick but further back into the engine compartment. Some vehicles do not have a normal dipstick. For those, the product has to be added to the transmission through a fill plug. Consult owner's manual for location. If fluid is low, pour entire contents of the bottle into the dipstick tube. **Do NOT** overfill. For compact and smaller vehicles, use ½ of the bottle. Tip. If necessary, to prevent overfill, drain some fluid from transmission. Check fluid level again. Top off with manufacturer's recommended transmission fluids as needed. Replace dipstick and drive 10 to 15 minutes to circulate fluid.

*How much do I install?*

The 32 oz Rislone Transmission Stop Slip with Leak Repair, part number 4502, is designed to treat 12 to 16 quarts of transmission fluid. For compact and smaller vehicles, use ½ of the bottle.

*Will Rislone Transmission Stop Slip with Leak Repair harm my transmission?*

No, the product is completely safe to use and will not harm any part of the transmission system.

*Can I use in a manual / standard "stick" transmission?*

Yes, the Rislone Transmission Stop Slip with Leak Repair will work in manual / standard "stick" transmissions to top off the fluid level to stop leaks, noise and grinding gears.