



ISO 9001:2000 CERTIFIED

BAR'S LEAKS TECHNICAL BULLETIN

Tech Bulletin #: TB-PLT11-1

Page 1 of 1

Date 1st Issued: June 1, 2006

Date Revised: November 27, 2007

Bar's Leaks Pelletized Stop Leak

Part #: PLT11

PELLETIZED STOP LEAK

Bar's Leaks Pelletized Stop Leak seals internal, external and coolant-to-oil leaks. It is specially formulated to seal larger leaks better than other stop leak products. Compatible with both conventional green (silicate-bases) and extended life red/orange or yellow (OAT) antifreeze. Works safely and effectively on plastic, aluminum and metal radiators, heater cores, blocks, heads, gaskets and freeze plugs. Lubricates water pump seal and inhibits the formation of rust and scale.



MOST COMMON COOLING SYSTEM PROBLEMS

- Radiator Leak
- Freeze Plug Leak
- Gasket Leak
- Head Leak
- Block Leak
- Heater Core Leak

THE SOLUTION, BAR'S LEAKS PELLETTIZED STOP LEAK

- Seals Leaks
- Conditions System
- Inhibits Rust and Corrosion
- Prevents Corrosion
- Lubricates Water Pump Seals
- Helps Control Electrolysis

DIRECTIONS

1. Cooling systems that are dirty or partially clogged should be flushed before usage.
2. Allow engine to cool so radiator cap can be safely removed.
3. Shake well and pour directly into radiator. Do not pack pellets in radiator. Pellets may be pre-dissolved if necessary by putting them in hot water. Note: If you don't have access to radiator, remove top hose where it connects to top of radiator and install product in hose. Reattach hose and tighten clamp.
4. Fill radiator and overflow tank to proper level, reinstall radiator cap and drive or idle engine for 15-30 minutes.
5. Leave Bar's Leaks in cooling system for preventative maintenance. Use once a year to help guard against future leaks.

Part Number: PLT11
 UPC Item: 0 46087 000047 2
 UPC Case: 1 00 46087 00047 9
 Bottle Size: 11 fl. oz. (325ml)
 Bottle Dimensions: 2.6 x 2.6 x 6.1
 Bottle Cube: 41
 Case Pack: 6 bottles per case
 Case Size: 5.4 x 7.8 x 6.8
 Case Cube: 286
 Case Weight: 6 pounds
 Pallet: TI 35 HI 7 Total 245
 Pallet Height: 52 inches
 Tariff Code: 2710.19.3070

DOSAGE

Use 1 bottle for 6, 8 and 10 cylinder gas or diesel engines. For 4 cylinder engines, use ½ of liquid and pellets. One bottle treats systems up to 4 gallons.