



# BAR'S LEAKS TECHNICAL BULLETIN

Tech Bulletin #: TB-T20L-1

Page 1 of 1

Date 1<sup>st</sup> Issued: June 2, 2006

Date Revised: November 27, 2007

ISO 9001:2000 CERTIFIED

Bar's Leaks Transmission Stop Leak

Part #: T20L

## TRANSMISSION STOP LEAK

Bar's Leaks Transmission Stop Leak is designed to stop leaks due to drying, hardening or shrinking of transmission seals and gaskets. Will not harm transmission and is compatible with ALL types of transmission fluid. Bar's Leaks Stop Leak helps your transmission last longer. Most leaks stop in 250 miles or 3 days of driving.



MOST COMMON TRANSMISSION PROBLEMS	THE SOLUTION, BAR'S LEAKS TRANSMISSION STOP LEAK
<ul style="list-style-type: none"> <li>Leaks</li> <li>Worn/Dry Seals</li> </ul>	<ul style="list-style-type: none"> <li>Stops Leaks</li> <li>Prevents Leaks</li> <li>Conditions Seals</li> </ul>

### DIRECTIONS

Add entire bottle of Stop Leak to restore transmission Fluid. Do not overfill system.

### INGREDIENTS

- Hydrotreated Oil
- Seal Swell
- Seal Conditioners

Part Number: T20L  
 UPC Item: 0 46087 00041 0  
 UPC Case: 1 00 46087 00041 7  
 Bottle Size: 15.5 fl. oz. (458ml)  
 Bottle Dimensions: 3.4 x 1.6 x 8.1  
 Bottle Cube: 44  
 Case Pack: 6 bottles  
 Case Size: 7.8 x 5.0 x 8.8  
 Case Cube: 321  
 Case Weight: 6.5 pounds  
 Pallet: TI 50 HI 5 Total 250  
 Pallet Height: 48 inches  
 Tariff Code: 2710.19.3020

### DOSAGE

One bottle treats 8 (eight) to 10 (ten) quarts of fluid.